



PORTABLE AIR MOVER

FDK SERIES

The Fam's multipurpose design allows it to be more powerful yet smaller than a common air mover in its class. Due to its lightweight compact size, the Fam is easy to carry and occupies less space when stored. It is very strong shock resistant thanks to the PE rotomolded case.

FEATURES

FRAME

"Very strong shock resistant PE rotomoulded case"

For Heavy Duty use.

Very long supply cable

Three flexible pipe adapter (Available only for FAM400 and FAM700).

USED MAINLY IN:

- Restoration;
- Drying Carpets;
- Building site works
- Hiring
- Drying of new house
- Basements

TECHNICAL DATA:	FAM200	FAM400	FAM700
Power Consumpt. - Max Speed	100 W	360 W	1200 W
- Normal Speed	-	-	950 W
- Low Speed	-	280	700 W
Absorbed Current - Max Speed	0.6A	3.6A	5.6 A
- Normal Speed	-	-	4.3 A
- Low Speed	-	2.5A	3.8 A
Fan speed : - Max Speed	1300 RPM	980 RPM	1400 RPM
- Normal Speed	-	-	1250 RPM
- Low Speed	-	650 RPM	950 RPM
Air Volume : - Max Speed	480 cm/h	1950 cm/h	6200 cm/h
- Normal Speed	-	-	4900 cm/h
- Low Speed	-	1200 cm/h	3400 cm/h
Air Speed: - Max Speed	9.8 m/s	16 m/s	27 m/s
Supports:	Sleeve	Ball bearings	Ball bearings
Power cable Standard Shucko (UK on request):	7 m	7 m	7 m
Weight:	3,5 kg	10,5 kg	17 kg
Box Size LxDxH mm	275x316x345	500x440x415	500x500x545
Numbers of unit in 20'container	1250	310	250
Numbers of unit in 40'container	2500	670	520



APPLICATIONS

SWIMMING POOLS

ARCHIVES

GYMS

HOUSES

BASEMENT ROOMS

LAUNDRY

RENTAL

HOTELS